

14AWG / 2C OFC STRANDED RISER (CMR) AUDIO CABLE



Cable Detail



Approval



Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	14
Stranding	105
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.1023 (inches)
Average Thickness	0.014 (inches)
Min. Point Thickness	0.013 (inches)
Assembly Diameter	0.2047 (inches)
Jacket Material	PVC
Outer Diameter	0.2519 (inches)
Average Thickness	0.0236 (inches)
Min. Point Thickness	0.02126 (inches)
Rip Cord	Nylon
Conductor Resistance	9.2 (ohms)
Nominal Weight	22 (pounds)
Voltage Rating	300V (volts)

Description

- 14/2 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Colors

- Insulation Color
Black / Red
- Jacket Color
Black, White

Part Number

AC1402RBK4-500
AC1402RWH4-500

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 2 COND 14AWG HI-STRAND OFC
CMR/CL3R FT4 75C EXXXXXX C(ETL)US ***FT

