

# 14AWG/4C STRANDED AUDIO CABLE UV RATED DIRECT BURIAL OUTDOOR



## Cable Detail



## Approval

- CM CL2/CL3 APPROVAL

## Applicable Standards

- Multi-conductor-audio/sound, control, instrumentation & LED lighting cables

## Physical Characteristics

<b>Construction</b>	
4 core	Oxygen Free Copper Wire Strands
AWG	14 / 2.11mm.sq
Stranding (wire NO/wire dia.mm)	105 / 0.16
<b>Insulation</b>	
<b>Binding Tape</b>	Paper Tape
Coverage (%)	+/- 125%
Thickness (mm)	0.4
Insulation Diameter (mm)	2.7 +/- 0.2mm
<b>Rip Cord</b>	
Material	Nylon (210D)
<b>Jacket</b>	
Material	Glossy PVC
Nominal Thickness (mm)	0.88 +/- 0.2
Cable Dia. (mm)	8.4 +/- 0.3

## Colors

- Insulation Color  
Black / Red / White / Green
- Jacket Color  
Black, White

## Part Number

AC1404HFXMBK4-500  
AC1404HFXMWH4-500

## Package

500FT / REELEX II

## Cable Marking

14-4 HFX AUDIO CABLE DIRECT BURIAL EXXXXXX (UL)  
CL3 C(UL) CM 14AWG 4C (ROHS) OXYGEN FREE COPPER  
ZONE/DEVICE A B C D E 1 2 3 4 6 7 8 9 \*\*\*FT

